



Height, width and tilt: All adjustable.

The **Universal Stand** can fit almost any small or mid-sized lathe with user-supplied adapter boards. Robust's 14" **Scout** lathe bolts on directly.

ROBUST 
UNIVERSAL STAND

The Universal Stand height can be adjusted for almost any turner, short or tall (Apr. 38-50" spindle heights). The stand will also lower and tip forward up to 30° for a seated turner.

Assembles with just two wrenches. Tool racks are built in. Casters are optional.

Critical Adjustments: Height adjusts: 22 - 34.5" (56 - 87.5cm). Add lathe height to get spindle height. Stand base is 28 .25" (71.5cm) front to back. Distance between mounting holes on top: 28.5 - 43.5" (72 - 110.5 cm). Overall length across top: 38.5 - 53.5" (98 - 136cm). Overall width at feet is 30.5 - 46.5" (77.5-118cm). Top tilts forward 0° to 30° in 7.5° increments.



Universal Stand Case Study:

The Universal Stand adapted to fit a Nova DVR lathe with user-supplied adapter boards and lag bolts. Other lathes, from minis to medium sized lathes can be adapted.



Lowered and tilted forward for the seated turner.



Top adjusts from 0° to 30° for the seated turner.

Robust Tools, LLC
www.turnrobust.com
 Toll Free US: 866-630-1122
 International: 608-924-1133
 Email: info@turnrobust.com



Raised and level for the standing turner.