



Height, width and tilt: All adjustable.

The **Universal Stand** can fit almost any small or mid-sized lathe with user-supplied adapter boards.

Robust's 14" **Scout** lathe bolts on directly .

The Universal Stand height can be adjusted for almost any turner, short or tall (Apr. 38-50" spindle heights). The stand will also lower and tip forward up to 30° for a seated turner.

Assembles with just two wrenches. Casters are optional.

**Please note:** Adjusting the height after assembly requires removal of the lathe and disassembly of the stand.



# UNIVERSAL STAND

**Critical Adjustments:** Height from floor to top of stand adjusts 22" - 34.5". Add you lathe height to get spindle height. Base is 28 .25" front to back. Distance between mounting holes on top: 28.5 - 43.5". Overall distance across top: 38.5 - 53.5" Overall width at feet is 30.5 - 46.5". Top tilts forward 0° to 30° in 7.5° increments.



### Universal Stand Case Study:

The Universal Stand adapted to fit a Nova DVR lathe with user-supplied adapter boards and lag bolts. Other lathes, from minis to medium sized lathes can be adapted.



Lowered and tilted forward for the seated turner.



Top adjusts from 0° to 30° for the seated turner.

**Robust Tools, LLC**  
[www.turnrobust.com](http://www.turnrobust.com)  
 Phone: 608-924-1133  
 Email: [info@turnrobust.com](mailto:info@turnrobust.com)



Raised and level for the standing turner.